

STRIPPERS

Strippers Paint Removers

P.O. Box 6, Sudbury, Suffolk, CO10 6TW. Tel: 01787 371524 Fax: 01787 313944

www.stripperspaintremovers.com

USAGE DATA SHEET

PRODUCT: STRIPPER NB-510 **TYPE:** Solvent-based two part paint remover.

USES: For removing polythurethane finishes, bitumastic-type coatings, floor sealers and some of the harder-to-remove masonry paints.

METHOD OF USE:

Preparation: Ensure adequate through-draught ventilation. Do not use in confined or unventilated areas. The product is supplied in two parts and must be mixed thoroughly just before use. Add part 'B' (the Activator) to Part 'A'. (If a smaller amount of mixture is required, the mix ratio is 10 parts by volume of Part 'A' to one of Part 'B').NB The product, once mixed, should be used within 24 hours. The surface of the coating to be removed must be dry. The product will take longer to work in ambient temperatures below 10 degrees centigrade.

Application: Ensure adequate through draught ventilation. Apply by brush, spreader or suitable airless spray equipment. (Please ask for details of specification for airless sprayers.)

Do not use brushes with plastic bristles. The product must be applied **generously** – i.e. on vertical surfaces allow it to run over itself to form a thick layer. Brushing out too thinly will cause the volatile ingredients in the product to evaporate before they can work on the paint. A small area of the surface to be stripped should be tested first to determine the time necessary for the product to work. This will be from a few minutes, for very thin layers of general-purpose coatings, and up to 4 hours for specialised paint systems. Occasionally, unexpected and exceptional results are obtained leaving an application to work overnight but ambient conditions must be cool and windless. When using on floors, pour the product over a small area and allow it to find its own level. When it has worked, simply squeegee it along to the next area with a piece of cardboard. When using NB-510 indoors, ensure adequate through-draught ventilation. Always replace lid on container each time you have decanted contents.

Removal: The dissolved paint is then removed with a hot water pressure-washer. A cold water machine may be adequate, but hot water is usually quicker and more effective. When pressure-washing, avoid wetting the areas coated with the product until they are actually being cleaned by the jet of water. Hold the nozzle of the pressure-washer lance close enough to the surface for effective washing off of the paint residues but not so close that the water damages the substrate.

Where use of a pressure-washer is not practical, use a bucket of hot soapy water, a scrubbing brush or green, abrasive washing-up cloths, and a sponge. This will usually give good results on reasonably smooth substrates, but be aware that a jet of water is much more effective than the bristles of a brush for removing the dissolved paint from rough, porous surfaces.

N.B. Our VACWASH pressure-washer/vacuum cleaner attachment makes it possible to use a pressure washer in areas where the spray and run/off from a normal pressure-washer lance would be unacceptable.

COVERAGE: Approximately 1 litre per square metre per application.

COMPATABILITY: The product is compatible with most masonry and timber surfaces. Some plastics and enamels are damaged by the product. Always test a small area first. Polythene is compatible, making it a suitable material for masking, etc.

STORAGE: Store in a cool well ventilated area. Must not be exposed to frost or stored at temperatures in excess of 30 degrees centigrade. Do not leave containers in direct sunlight. Ensure containers are tightly closed.

HEALTH, SAFETY & FIRST AID:

Do not use in confined or unventilated areas. Ensure adequate through-draught ventilation. Suitable protective clothing must be worn when handling or using the product. For full health and safety information see Material Safety Data Sheet.

SKIN CONTACT: Splashes on the skin should be washed off immediately with plenty of water. Splashes and spillages on absorbent clothing should similarly be removed and washed out immediately.

EYES CONTACT. Flush the eye immediately with copious quantities of water. Ensure the eyelid is open and water is bathing the eye. Continue flushing for at least 15 minutes and seek medical attention.

INHALATION: Remove to fresh air, if not breathing administer artificial respiration. Seek medical attention

INGESTION: If swallowed, give plenty of water to drink and seek immediate medical treatment. Do NOT induce vomiting. Do NOT give an unconscious person anything to drink.

** Keep out of reach of children & animals

** Avoid contact with skin and eyes. Part 'A' Contains dichloromethane.

** Causes severe burns. Part 'B' contains formic acid.

** Wear rubber or pvc gloves and eye/face protection and suitable protective clothing

** Do not breath vapour.

** Do not smoke near the product.

** In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

For full health and safety information see Material Safety Data Sheet.