



**STRIPPERS
PAINT
REMOVERS**

PO Box 6, Sudbury, Suffolk, CO10 6TW
01787 371524 •
stripperspaintremovers.com

USAGE DATA SHEET

PRODUCT: OXALIC BLEACH - OXB.

TYPE: Oxalic acid granules.

APPLICATION: The removal of staining and lightening of wood.

DILUTION RATE:

For normal wood staining, use 100g of OXB in one litre of water.

For heavy staining on wood, use 200g of OXB in one litre of water.

Always replace lid on container each time you have decanted contents.

IMPORTANT: Always do a small test area first.

METHOD OF USE:

Ensure surface to be treated is cleaned thoroughly before application. Apply the dilute OXB solution with a brush and wipe off excess with a clean rag. If the surface is to be re-stained, you must neutralise areas treated with OXB using a borax or baking soda solution otherwise any stain applied may also be affected.

COVERAGE: 8-12 square metres per litre of dilute solution.

STORAGE: Store in a cool, dark, dry, well ventilated place, away from other chemicals.

SPILLAGE: Wash thoroughly with water.

HEALTH & SAFETY

Suitable protective clothing must be worn when handling or using the product. For full health and safety information see Health and Safety Data Sheet.

CAUTION:

- ** Use only with adequate ventilation.
- ** Do not mix in a metal container.
- ** Wear suitable gloves and eye and face protection.
- ** In case of contact with eyes. Rinse immediately with plenty of water and seek medical advice.
- ** Keep out of reach of children and animals.
- ** In case of accident or if you feel unwell, seek medical advice immediately.
- ** Do not mix with chlorine bleach or other cleaning products.