

STRIPPERS

Strippers Paint Removers

P.O. Box 6, Sudbury, Suffolk, CO10 6TW. Tel: 01787 371524 Fax: 01787 313944

USAGE DATA SHEET

PRODUCT: WOODBLEACH WB-1

TYPE: Two part wood bleach.

APPLICATION: For lightening the colour of wood and removing discolouration.

IMPORTANT: Do a small test area first.

METHOD OF USE: Apply PART 'A' using a brush with plastic bristles. Leave for 5 minutes. Wipe off any excess with a rag. Apply PART 'B' using another brush. Part 'B' should then start to fizz and bubble on the surface. This bleaching action may continue for up to 30 minutes, if wood is not light enough, repeat the treatment. Finish by washing surface with clean water. **Important:** If bleaching after removing paint with an alkali based stripper, or if repeating the treatment, PART 'B' may work adequately without first applying PART 'A'. Use separate containers and brushes for PART 'A' and PART 'B'. **DO NOT** mix the two parts.

COVERAGE: 9-14 square metres per litre.

STORAGE: Store in a cool, dark, dry, well ventilated place, away from other chemicals.

SPILLAGE: Wash thoroughly with water.

HEALTH & SAFETY

Suitable protective clothing must be worn when handling or using the product. For full health and safety information see Health and Safety Data Sheet.

CAUTION:

- ** Wear suitable gloves and eye and face protection
- ** Causes burns
- ** Keep out of reach of children and animals.
- ** In case of contact with eyes. Rinse immediately with plenty of water and seek medical advice.
- ** In case of accident or if you feel unwell, seek medical advice immediately.